




Original Dual Wire Ferrules



Dual Wire Insulated

Dual Wire Ferrules have larger diameters and special shaped barrels that accept two conductors of the same or different size. They provide an efficient connection of multiple wires in the same terminal clamp or simplify wire jumpering between terminal clamps. They are color coded with the same convention as the insulated DIN standard ferrules.

To ensure efficient ferrule crimping always select the smallest ferrule diameter that fits the wire and use only professional crimping tools.

- Sleeve: polypropylene
- Tube: tin plated copper



Tested According To:


CSA Std C22.2 No. 65-93
 CSA Std C22.2 No. 188-M1983
 ANSI/UL Std No. 486A
 ANSI/UL Std No. 486C

- Wire Connectors
- Splicing Wire and Cable Connectors
- Wire Connectors and Soldering Lugs for Use with Copper Conductors
- Splicing Wire Connectors

Wires x AWG	mm ²	Color	Cat. No.	Barrel Length (B) mm	Ferrule Dimensions mm	A	B	C	D1	D2	Std. Pack*
2x20	2x0.50	White	2794.0	11	14.6	8.2	1.7	3	5	500/100	
2x18	2x0.75	Gray	2775.0	11	14.6	8.2	2.0	3	5.5	500/100	
2x18	2x0.75	Gray	2795.0	13	16.4	10	2.0	3	5.5	500/100	
2x18	2x1	Red	2776.0	11	15.4	8.2	2.4	3.2	5.8	500/100	
2x18	2x1	Red	2796.0	21	25.2	18	2.4	3.2	5.8	500/100	
2x16	2x1.5	Black	2777.0	12	15.8	8.2	2.6	3.6	6.5	500/100	
2x16	2x1.5	Black	2797.0	16	19.6	12	2.6	3.6	6.5	500/100	
2x14	2x2.5	Blue	2778.0	14	18.5	10	3.3	4.5	8	500/100	
2x14	2x2.5	Blue	2798.0	17	20.5	12	3.3	4.5	8	500/100	
2x12	2x4	Gray	2799.0	16	22	12	3.9	5.2	9	100	
2x10	2x6	Yellow	2800.0	18	23	12	5	6.2	11.4	100	
2x8	2x10	Red	2801.0	18	24	12	6.2	7.6	13.4	100	
2x6	2x16	Blue	2802.0	20	29	16	8.9	9.5	17.2	100/50	

INSULATED FERRULES Assortment Box

Handy Assortment Boxes for convenient dispensing and storage of Industry and DIN Standard Insulated Ferrules. Types AB1-S and AB1-D are equipped with five different ferrule sizes. Types AB2-S and AB2-D are equipped with four different ferrule sizes. Contents of each box is listed.



* Different standard packs are available for many ferrules. To order the desired standard pack, please use the quantity required as a suffix to the Cat. No.

Example: Cat. No. 2794.0/100 for a standard pack of 100



AB1-S



AB2-S

CRIMPER SELECTOR GUIDE
page 18

Ferrule Qty.	AWG	mm ²	Ferrule Cat. No.	Ferrule Color	Type	Cat. No.	Std. Pack
AB1-S Industry Standard					AB1-S	2884.9	1
50	20	0.5	2201.0	Orange			
100	20	0.75	2202.0	White			
100	18	1	2399.0	Yellow			
100	16	1.5	2204.0	Red			
50	14	2.5	2206.0	Blue			
AB2-S Industry Standard					AB2-S	2885.9	1
50	12	4	2208.0	Gray			
20	10	6	2210.0	Black			
20	8	10	2212.0	Ivory			
10	6	16	2214.0	Green			
AB1-D DIN Standard					AB1-D	2884.0	1
50	20	0.5	2864.0	White			
100	20	0.75	2867.0	Gray			
100	18	1	2871.0	Red			
100	16	1.5	2841.0	Black			
50	14	2.5	2845.0	Blue			
AB2-D DIN Standard					AB2-D	2885.0	1
50	12	4	2848.0	Gray			
20	10	6	2851.0	Yellow			
20	8	10	2853.0	Red			
10	6	16	2855.0	Blue			