



Note:

All the electrical connections must either be isolated from the mains supply by a safety transformer according to IEC/EN 61558-2-6 with limited output voltage in the event of a fault, or by other equivalent isolation measures.

PIN	Connection/Signal
1	+24V
2	RxD
3	-0V
4	TxD

Technical Data

Parameter	Value		Unit
	min.	nom. max.	
General parameter	Plastic		
Housing	IP 65		
Environmental protection according IEC 60529			
Storage temperature	-25	+80	°C
Ambient temperature	0	+55	°C
Operating voltage U _B (regulated, residual ripple < 2%)	20	28	VDC
Permanent power consumption (without load)		140	mA
Connection type	Screw terminal		
Interface, data transmission, documentation			
Interface	RS 232 / V.24		
Protocol	3964R		
Data rate	9,6		kBaud
Parity	even		
Cable length (RS 232 - interface)		5	m

Ausg.	Änd.-Nr.	Datum	Name	Datum	Name
2	05161	08.04.05	BR	04.12.02	BR
			Geprüft	04.04.05	FK
			Genehmigt	B. t. 05	



**Technische Änderungen vorbehalten.
 Subject to technical modifications.**

Maßstab		/
Blatt		1
Benennung		077890
Zeichnung-Nr.		077890
Bemerkung		READ/WRITE-HEAD CIT3ASX1R1G05KX
Klasse-Nr.		1473