


## IRT/C.3SV

### Product Overview

The IRT/c.3SV features:

- Infrared Thermocouple IRT/c
- Non-contact
- Self-powered
- Intrinsically Safe
- Repeatability 0.02°F (0.01°C)
- Interchangeability ±1%
- Resolution approx. 0.0001°C
- Small Size




### Technical Data

Sensing Range	-50 to 1200°F (-45 to 650°C)	Dimensions	See diagram above
Ambient Temperature Range	0 to 248°F (-18 to 120°C)	Housing	Stainless steel, hermetically sealed, exceeds NEMA 4,4X; IP65, 67, cable shield grounded to housing and electrically isolated from signal
Optimum Range Selections	Eight models per t/c type (see Temperature Selection Chart)	Cable	Twisted shielded pair of base thermocouple material (J,K,E,T), 3ft (.9m) std length, Teflon sheathed, rated to 392°F (200°C) continuous service
Field of View	approximately 3:1 (17°)	Weight	1.6oz. (44 grams) with cable
Minimum Spot Size	.2" (5mm)	Air Purge	Built-in; designed for severe paint or ink environment; 3' (0.9 m) of tubing provided
Spectral Response	6.5 to 14μm		
Output Impedance	4 to 8 Kohms approx		
Response Time	100 Milliseconds		

### Calibration

Ordering information **IRT/c.3SV-\*** (Thermocouple Type) - (Precalibrated Temperature Range). Thermocouple type J,K,E,T over temperature range specified.

Temperature Selection Chart



Exergen Global offices:

The Netherlands  
 Pastoor Clercxstraat 26  
 5465 RH Veghel  
 Tel: +31 (0)413 376 599  
 Fax: +31 (0)413 379 310

USA  
 400 Pleasant Street  
 Watertown, MA 02472  
 Tel: +1 617 649 6322  
 Fax: +1 617 923 9911

Specifications subject to change without notice

office@exergenglobal.com  
 www.exergenglobal.com