

ODP-2-42100-3HF4A-MN

Optidrive P2 VFD Datasheet

10 HP, 30 A, 200-240 V, 3PH

IP66 Non Switched Outdoor Variable Frequency Drive with EMC Filter and TFT Display



Input Ratings

| | |
|-----------------------------|-----------|
| Supply Voltage | 200-240 V |
| Input Phases | 3 |
| Supply Current Continuous | 36.4 A |
| Supply Fuse or MCB (Type B) | 50 A |

Output Ratings

| | |
|---------------------|--------------------|
| Motor Output Rating | 7.5 kW (10 HP) |
| Output Voltage | 0 – Supply Voltage |
| Output Current | 30 A |

Cable Information

| | |
|------------------------|---------------------------------|
| Max Supply Cable Size | 16 mm ² (0.02 sq in) |
| Max Motor Cable Size | 16 mm ² (0.02 sq in) |
| Max Motor Cable Length | 100 m (328 ft) |

Factory Build Options

| | |
|------------------|---------------------------|
| EMC Filter | Internal EMC |
| Brake Transistor | Internal |
| Enclosure | IP66 Non Switched Outdoor |
| Display | TFT Display |
| PCB Coating | Standard |


Dimensions

| | |
|---------|--------------------|
| Size | 4 |
| Height | 360 mm (14.17 in) |
| Width | 240 mm (9.45 in) |
| Depth | 261 mm (10.28 in) |
| Weight | 9.5 kg (20.94 lbs) |
| Fixings | 4 x M4 |

Packaged Dimensions

| | |
|--------|---------------------|
| Height | 325 mm (12.8 in) |
| Width | 295 mm (11.61 in) |
| Depth | 425 mm (16.73 in) |
| Weight | 11.5 kg (25.35 lbs) |



 **Buy this drive or get more information**
Find your local sales partner on
invertekdrives.com



How we measure our drives and packaging



Drive Dimensions



Packaging Dimensions



Buy this drive or get more information

Find your local sales partner on
invertekdrives.com

