

The H100 VFD satisfies the spectrum of HVAC applications. It combines air and water into a single VFD product iteration.

End users and system designers will both enjoy the inherent value in the H100's standard configuration. *Consider two examples....*

Can your HVAC drive operate in a **pollution degree 3 environment** without the expense of optional conformal coating? **The H100 can.**

Does your HVAC drive come with **5 relay outputs as standard**, eliminating the need for option cards sometimes required in sophisticated installations? **The H100 does.**

SOFTWARE FEATURES

Real Time Clock	Fire Mode
Underload	Soft Pipe Fill
Broken Belt / Pipe	Pump Clean
Flow Compensation	Multi Motor Control
Payback Counter	Damper Lubrication



External PID
Check Valve Ramp
Sleep Mode
Level Detection
Bypass Option

LSIS USA, INC. Lincolnshire, IL 60069 847.941.8244 www.lsis.com/usa

For more information please contact



240 VAC (-15% to +10%) 3 phase

Model Number	НР	Amps	н	W	D
LSLV0008H100	1	5.0	9.1	6.3	7.1
LSLV0015H100	2	8.0			
LSLV0022H100	3	12.0			
LSLV0037H100	5	16.0			
LSLV0055H100	7.5	22.0			
LSLV0075H100	10	30.0			
LSLV0110H100	15	42.0			
LSLV0150H100	20	56.0	11.4	7.1	8.1
LSLV0185H100	25	69.0	13.8	8.7	8.8

480 VAC (-15% to +10%) 3 phase (EMC filter available)

Model Number	HP	Amps	Н	W	D		
LSLV0008H100	1	2.5	9.1		7.1		
LSLV0015H100	2	4.0		6.3			
LSLV0022H100	3	6.0					
LSLV0037H100	5	8.0					
LSLV0055H100	7.5	12					
LSLV0075H100	10	16					
LSLV0110H100	15	24					
LSLV0150H100	20	30	11.4	7.1	8.1		
LSLV0185H100	25	38					
LSLV0220H100	30	45	13.8	8.6	8.8		
LSLV0300H100	40	61					
LSLV0370H100	50	75	17.7	10.8			
LSLV0450H100	60	91	20.1	12.1	11.2		
LSLV0550H100	75	107					
LSLV0750H100	100	142	21.7	12.1	12.8		
LSLV0900H100	125	169					

Also Available Flange Kit



Conduit Kit (UL Type 1 Plenum Rated)





LSIS USA, INC. Lincolnshire, IL 60069 847.941.8244 www.lsis.com/usa