

Technical data sheet - LÜTZE SILFLEX® N (C) PVC CONTROL TRAY CABLE

With approvals for North America according to NEC, NFPA 79 and UL 508A



PVC control cables · shielded

Identification	Type	SI N (C)PVC TRAY-ER (7xAWG16)GR
	Part-No.	A3091607

Use/Application/Characteristics

Application	<ul style="list-style-type: none"> • Multi-conductor control cables with TC-ER „Exposed Run“ approval • Machine and device construction, HVAC technology, heating and climate technology • Compliant with NFPA 79 standards • „TC-ER“ for use on machines and in open cable ducts • „WTTC“ Wind Turbine Tray Cable for use in wind turbines • „MTW“ Machine Tool Wire • „PLTC-ER“ Power Limited Tray Cable – Exposed Run • „ITC-ER“ Instrumentation Tray Cable • In dry, moist and wet rooms
Characteristics	<ul style="list-style-type: none"> • Flexible wires with nylon for better resistance to pressure and impacts as per UL 1277 • Easy stripping and fast installation • Very flexible flexibility for complex installation distances and small bending radii • Improved oil resistance due to specifically developed PVC jacket • Sunlight-resistant • „Direct burial“ for installation in the ground • Silicone free • RoHS compliant

Construction

28.11.2017 – Subject to technical modification

Part-No. A3091607

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
 Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
 www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
 Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
 Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
 www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet - LÜTZE SILFLEX® N (C) PVC CONTROL TRAY CABLE

With approvals for North America according to NEC, NFPA 79 and UL 508A

Description	SILFLEX CONTROL CABLE (C) PVC
Number of conductors/cross-section	(7xAWG16)
Jacket material	PVC
Jacket color	grey RAL 7001
Outer Ø	10.9 mm
Outer Ø	0.43 inches
Weight	21.5 kg/100 m
Weight	145 Lbs/Mft
Cu-Index	11.2 kg/100 m
Cu-Index	75 Lbs/Mft

Element 1

Element construction	AWG16/7C
Conductor construction	AWG 16 (26/30)
Conductor	AWG conductor CU-wire bare
Conductor category	fine wire
Conductor marking	black with white number print green/yellow
Conductor insulation	PVC/Nylon THHN – THWN

overall construction

Drain wire	CU-wire tin-plated
Overall shield	Aluminium laminate Foil shield Braid shield Tinned copper wires
Jacket characteristics	Oil resistant Silicone-free

Technical data

Rated voltage	600 V TC-ER/MTW 1000 V WTTC
Temperature range fixed	-40 °C ... +90 °C
Minimum bending radius fixed	6xD

Element 1

Element construction	AWG16/7C
----------------------	----------

Approvals/Standards

28.11.2017 – Subject to technical modification

Part-No. A3091607

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY

Technical data sheet - LÜTZE SILFLEX® N (C) PVC CONTROL TRAY CABLE


With approvals for North America according to NEC, NFPA 79 and UL 508A

Approvals	TC-ER WTTC UL Type MTW or DP-1 Class 1 Div. 2 per NEC Art. 336, 392, 501 cUL TC CIC FT4 UL 1277 PLTC-ER ITC-ER
UL style	AWM 20886
Conformity	CE REACH RoHS
Oil resistant according to	Oil Res II

General

Note These products are in conformity with the EU Low Voltage Directive 2006/95/EC

Symbols



28.11.2017 – Subject to technical modification

Part-No. A3091607

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk



SYSTEMATIC TECHNOLOGY