



# Cable Glands

## Metric Threads Cable Glands



Standard Plastic Cable Glands | Metric Threads | IP68 Rating





Part Number		UL Rating	Diameter Range (mm)	A Mounting Hole Clearance (mm)	B Thread Length (mm)	C Wrench Flats (mm)	Thread Type
Gray	Black						
PCG-M12R	PCG-M12R-B	N/A	2 - 5	12.2	8	15	M12 x 1.5
PCG-M12	PCG-M12-B	UL Recognized	3 - 6.5	12.2	8	15	M12 x 1.5
PCG-M16R	PCG-M16R-B	N/A	3 - 7	16.2	8	22	M16 x 1.5
PCG-M16	PCG-M16-B	UL Recognized	5 - 10	16.2	8	22	M16 x 1.5
PCG-M20R	PCG-M20R-B	UL Recognized	5 - 9	20.2	8	24	M20 x 1.5
PCG-M20	PCG-M20-B	UL Listed	10 - 14	20.2	8	27	M20 x 1.5
PCG-M25R	PCG-M25R-B	N/A	9 - 16	25.2	8	33	M25 x 1.5
PCG-M25	PCG-M25-B	UL Recognized	13 - 18	25.2	8	33	M25 x 1.5
PCG-M32R	PCG-M32R-B	UL Listed	12 - 20	32.2	10	42	M32 x 1.5
PCG-M32	PCG-M32-B	UL Listed	18 - 25	32.2	10	42	M32 x 1.5
PCG-M40R	PCG-M40R-B	UL Listed	20 - 26	40.2	10	53	M40 x 1.5
PCG-M40	PCG-M40-B	UL Listed	22 - 32	40.2	10	53	M40 x 1.5
PCG-M50R	PCG-M50R-B	UL Listed	25 - 31	50.2	12	60	M50 x 1.5
PCG-M50	PCG-M50-B	UL Listed	30 - 38	50.2	12	60	M50 x 1.5
PCG-M63R	PCG-M63R-B	UL Listed	29 - 35	63.2	12	65	M63 x 1.5
PCG-M63	PCG-M63-B	UL Listed	34 - 44	63.2	12	65	M63 x 1.5

The Flex Style Version of UL recognized & UL listed parts are also UL recognized and UL listed. For the flex style version, add "S" to the part number (e.g. PCG-M25-BS). Flex styles are not available on the PCG-M32 to PCG-M63 versions.

Mencom Cable Glands are easy to use and provide a good strain relief and water tight seal for round cables. The cable glands are rated up to IP68-5 Bar (comparable to NEMA 6P). The glands have a wide clamping range.

A Locking Nut is supplied on all Metric threaded parts. O-Rings are not required to maintain a seal on any sizes smaller than M32. An O-Ring is supplied on size M32 and larger.



Cable Glands & Adapters

U

### Materials:

Body: Polyamide  
Seal: Neoprene