## **GATEWAYS Selection Guide**







**AirGate Modbus** 





1		
	9	
	2	ľ
	novnz	

		$\mathbb{V}$	U	
We Me	easure, We	e Cont	rol, We	Record

Gateway Type
Communication Interfaces
Isolation
Protocols
Network Topology
Wireless Features
Security Features
Modes of Operation
Additional Features
Firmwre Upgrade
Power Supply
Programmable Functions
Configuration
Housing
Dimensions
Operating Range
Protection Rating
Electric Protection
0 115 11

USB	i485	Converter

Wired	Wireless
USB and RS485 / RS422	USB, RS485 and IEEE802.15.4
Between USB and RS485 / RS422	Between Profibus and the rest of device
Modbus RTU	Modbus RTU and Novus-Air
Bus	Point-to-point, star and tree
	ISM 2.4 GHz, DSSS, OQPSK, 15 channels, Tx Power 20dBm, Sensitivity -96dBm, Line-of-Sight Range 1000 m
	AES-CBC-128 Encryption
Automatic detection by PC	RS485-Master, USB-Master, Multi-Master, RS485-Slave
	USB
5 V by USB Connection	10 ~ 35 Vdc
	Mode of Operation and Communication Settings
	USB with DigiConfig
Injected in ABS	Injected in PA66
70 x 60 x 18 mm	99.5 x 114 x 17.5 mm
Temperature 0 to 50 °C Humidity 10 to 90%	Temperature 0 to 70 °C Humidity 80% up to 30 °C
IP20	IP20
Bus overvoltage and ESD	Reverse Polarity
CE	Anatel, CE, FCC

DigiGate Profibus	AirGate 3G
Wired	Wireless
RS485 and Profibus	USB, RS232, RS485, 2 x Ethernet, GPS and 3 G
On Ethernet, Digital Inputs and Outputs	On Ethernet, Digital Inputs and Outputs
Modbus RTU and Profibus DP	Modbus RTU / ASCII, ModbusTCP, Novus Cloud, TCP Client / Server, UDP
Modbus: Point-to-multipoint Profibus: Bus	Several topologies (See Manual)
	GPRS / EDGE: 850 / 900 / 1900 / 2100 MHz, HSPA+: 850 / 900 / 1900 / 2100 MHz, DL / UL 21 / 5.76 Mbps or 2 G
	VPN tunnel (IPSec / OpenVPN / PPTP / L2TP / GRE)
Modbus-Master and Profibus-Slave	Gateway between Modbus RTU / ASCII and Modbus TCP, VPN Tunnel, 3G Data Logger
	GPS, Alam by SMS, Dual SIMCARD, Memory SD Card, 2 Digital Inputs with Counter, 2 Digital Outputs, RTC
	USB and WEB
10 ~ 35 Vdc	9 ~ 60 Vdc
Scan Rate and Communication Settings	See Manual
RS485 with DigiConfig	WEB browser
Injected in PA66	Metal Box
99.5 x 114 x 22.5 mm	125 x 108 x 45 mm
Temperature 0 to 50 °C Humidity 30 to 80%	Temperature -40 to 85 °C Humidity 5 to 95%
IP20	IP20
Bus overvoltage and ESD	Bus overvoltage and ESD
	Anatel, CE, FCC