

PFH-T | COMPACT FAN HEATER WITH THERMOSTAT

200 W - 1200 W

NEW



UL US CE

The PFH-T Series Compact Fan Heaters with thermostat feature our **new touch safe design**. Ideal for maintaining precise temperatures required for the proper function of electronics, while also protecting equipment from damaging condensation caused by changes in temperature or humidity. **Available in 6 models.**

Flexible Mounting Options

Unit can be direct mounted or connected to a standard DIN rail **without tools** using the included snap fastener.

Compact Design

Wide range for heat options from 200W to 1200W all housed in the same compact housing.

Touch-Safe Outer Housing

Well insulated ABS high-temperature resistant plastic housing material ensures that unit remains cool and safe to touch during operation.

Integrated Fan

Compact fan moves air across the heater elements to provide quick and efficient heating of the enclosure.

Precise Temperature Control

Built in thermostat allows our heater to be set to the precise temperature required for your application.

UL Certified

Heaters are UL Recognized to NITW2 and NITW8 standards allowing for easy integration into UL 508A panels.

Reduced Installation Time

Save time and money when installing or moving the unit with our UL listed quick connects.

PTC Heater Technology

Uses a self regulating heating element designed to prevent overheating and safe operation within your application.

PFH-T Series (200 - 1200 W) Compact Fan Heaters

Model Number	Part Number	Voltage (VAC)	Heating performance (W)*	Frequency (Hz)	Power Consumption (W)	Airflow Volume CFM (m3/h)	Starting Current (A)	Width in (mm)	Depth in (mm)	Height in (mm)	Weight (kg)
PFH-T 200	17020715034	115	200	60	215	30 (50)	9	3.46 (88)	5.47 (139)	5.59 (142)	1.68 (.76)
	17020710034	230	200	50/60	215	30 (50)	9	3.46 (88)	5.47 (139)	5.59 (142)	1.68 (.76)
PFH-T 400	17040715034	115	400	60	415	30 (50)	15	3.46 (88)	5.47 (139)	5.59 (142)	1.68 (.76)
	17040710034	230	400	50/60	415	30 (50)	15	3.46 (88)	5.47 (139)	5.59 (142)	1.68 (.76)
PFH-T 650	7065715034	115	650	60	665	30 (50)	20	3.46 (88)	5.47 (139)	5.59 (142)	1.68 (.76)
	17065710034	230	650	50/60	665	30 (50)	20	3.46 (88)	5.47 (139)	5.59 (142)	1.68 (.76)
PFH-T 800	17080715034	115	800	60	815	30 (50)	31	3.46 (88)	5.47 (139)	5.59 (142)	1.68 (.76)
	17080710034	230	800	50/60	815	30 (50)	31	3.46 (88)	5.47 (139)	5.59 (142)	1.68 (.76)
PFH-T 1000	17099715034	115	1000	60	1015	47 (80)	25	3.46 (88)	5.47 (139)	5.59 (142)	1.68 (.76)
	17099710034	230	1000	50/60	1015	47 (80)	25	3.46 (88)	5.47 (139)	5.59 (142)	1.68 (.76)
PFH-T 1200	17099810034	230	1200	50/60	1215	47 (80)	31	3.46 (88)	5.47 (139)	5.59 (142)	1.68 (.76)

Design

Housing: ABS high temperature plastic