



MZM 100 ST-SD2PR-A

- Power to lock
- Guard locking monitored
- Connector M23, 8+1-pole
- serial diagnostic output
- Automatic latching
- Solenoid interlocks with innovating and unique operating principle
- 40 mm x 179 mm x 40 mm
- Electronic contact-free, coded system
- Thermoplastic enclosure
- Max. length of the sensor chain 200 m
- 3 LEDs to show operating conditions
- Sensor technology permits an offset between actuator and interlock of ± 5 mm vertically and ± 3 mm horizontally
- Intelligent diagnosis
- Self-monitoring series-wiring
- Patented

Data

Ordering data

Product type description	MZM 100 ST-SD2PR-A
Article number (order number)	101187451
EAN (European Article Number)	4030661343440
eCl@ss number, version 12.0	27-27-26-03
eCl@ss number, version 11.0	27-27-26-03
eCl@ss number, version 9.0	27-27-26-03
ETIM number, version 7.0	EC002593
ETIM number, version 6.0	EC002593

Approvals - Standards

Certificates	TÜV cULus UKCA
--------------	----------------------

General data

Standards	EN ISO 13849-1 EN ISO 14119 EN IEC 60947-5-3 EN IEC 61508
Coding	Universal coding
Coding level according to EN ISO 14119	Low
Working principle	inductive
Housing material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Reaction time, maximum	150 ms
Duration of risk, maximum	150 ms
Gross weight	625 g

General data - Features

Power to lock	Yes
Solenoid interlock monitored	Yes
Serial diagnostics	Yes
Latching	Yes
Short circuit detection	Yes
Cross-circuit detection	Yes
Series-wiring	Yes
Safety functions	Yes
Integral system diagnostics, status	Yes
Number of safety contacts	2

Number of series-wiring of
sensors 31

Safety classification

Standards EN ISO 13849-1
EN IEC 61508

Safety classification - Interlocking function

Performance Level, up to e
Category 4
PFH value $3.54 \times 10^{-9} /h$
Safety Integrity Level (SIL), 3
suitable for applications in
Mission time 20 Year(s)

Mechanical data

Mechanical life, minimum 1,000,000 Operations
Note (Mechanical life) Actuating speed ≤ 0.5 m/s
Operations for door weights ≤ 5 kg
Holding force, typically 750 N
Holding force, guaranteed 500 N
Latching force 30 N
Type of the fixing screws 2x M6
Tightening torque of the fixing screws 8 Nm

Mechanical data - Switching distances according EN IEC 60947-5-3

Assured switching distance 0 mm
"ON" S_{ao}

Assured switching distance "OFF" S_{ar}	1 mm
--	------

Mechanical data - Connection technique

Length of sensor chain, maximum	200 m
Note (length of the sensor chain)	Cable length and cross-section change the voltage drop depending on the output current
Note (series-wiring)	Unlimited number of devices, observe external line fusing, max. 31 devices in case of serial diagnostic SD
Termination	Connector M23, 8+1-pole

Mechanical data - Dimensions

Length of sensor	40 mm
Width of sensor	40 mm
Height of sensor	179 mm

Ambient conditions

Degree of protection	IP65 IP67
Ambient temperature	-25 ... +55 °C
Storage and transport temperature, minimum	-25 °C
Storage and transport temperature, maximum	+70 °C
Relative humidity, minimum	30 %
Relative humidity, maximum	95 %
Note (Relative humidity)	non-condensing non-icing
Resistance to vibrations	10 ... 150 Hz, amplitude 0.35 mm / 5 g
Resistance to shock	30 g / 11 ms

Protection class	III
Permissible installation altitude above sea level, maximum	2,000 m

Ambient conditions - Insulation values

Rated insulation voltage U_i	32 VDC
Rated impulse withstand voltage U_{imp}	0.8 kV
Overvoltage category	III
Degree of pollution	3

Electrical data

Operating voltage	24 VDC -15 % / +10 % (stabilised PELV power supply)
No-load supply current I_0 , typical	100 mA
Current consumption with magnet ON, average	350 mA
Current consumption with magnet ON, peak	550 mA / 10 ms
Rated operating voltage	24 VDC
Operating current	1,100 mA
Required rated short-circuit current	100 A
External wire and device fuse rating	2 A gG
Time to readiness, maximum	4,000 ms
Switching frequency, maximum	1 Hz

Electrical data - Magnet control

Designation, Magnet control	IN
-----------------------------	----

Switching thresholds	-3 V ... 5 V (Low) 15 V ... 30 V (High)
Current consumption at 24 V	10 mA
Magnet switch-on time	100 %
Test pulse duration, maximum	5 ms
Test pulse interval, minimum	40 ms
Classification ZVEI CB24I, Sink	C0
Classification ZVEI CB24I, Source	C1 C2 C3

Electrical data - Safety digital inputs

Designation, Safety inputs	X1 and X2
Switching thresholds	-3 V ... 5 V (Low) 15 V ... 30 V (High)
Current consumption at 24 V	5 mA
Test pulse duration, maximum	1 ms
Test pulse interval, minimum	100 ms
Classification ZVEI CB24I, Sink	C1
Classification ZVEI CB24I, Source	C1 C2 C3

Electrical data - Safety digital outputs

Designation, Safety outputs	Y1 and Y2
Rated operating current (safety outputs)	250 mA
Design of control elements	short-circuit proof, p-type
Voltage drop U_d , maximum	1 V
Leakage current I_r , maximum	0.5 mA
Voltage, Utilisation category DC-13	24 VDC

Current, Utilisation category DC- 0.25 A

13

Test pulse interval, typical 1000 ms

Test pulse duration, maximum 1 ms

Classification ZVEI CB24I,
Source

Classification ZVEI CB24I, Sink C1

Electrical data - Diagnostic outputs

Design of control elements short-circuit proof, p-type

Electrical data - Serial diagnostic SD

Designation, Serial diagnostic SD OUT

Operation current 150 mA

Design of control elements short-circuit proof, p-type

Wiring capacitance 50 nF

Status indication

Note (LED switching conditions display) Operating condition: LED green
Error / functional defect: LED red
Supply voltage UB: LED green

Pin assignment

PIN 1 A1 Supply voltage UB

PIN 2 X1 Safety input 1

PIN 3 A2 GND

PIN 4 Y1 Safety output 1

PIN 5 OUT serial diagnostic output

PIN 6 X2 Safety input 2

PIN 7	Y2 Safety output 2
PIN 8	IN serial diagnostic input
PIN 9	without function

Scope of delivery

Scope of delivery Actuator must be ordered separately.

Accessory

Recommendation (actuator) MZM 100-B1.1

Note

Note (General) As long as the actuating unit is applied to the solenoid interlock, the unlocked safety guard can be relocked. In this case, the safety outputs are re-enabled, so that the safety guard must not be opened.

Ordering code

Product type description:

MZM 100(1)(2)(3)(4)(5)-A

(1)

without Solenoid interlock monitored

B Actuator monitored

(2)

ST2 Connector plug M12, 8-pole

ST Connector plug M23, 8+1-pole

(3)

1P2P 1 p-type diagnostic output and 2 p-type safety outputs
(only in connection with "Solenoid interlock monitored")

1P2PW

Similar to -1P2P, combined diagnostic signal: guard door closed and solenoid interlock locked (only in connection with "Solenoid interlock monitored")

1P2PW2

Similar to -1P2P, combined diagnostic signal: guard door closed and can be locked (only in connection with "Actuator monitored")

SD2P

serial diagnostic output and 2 p-type safety outputs

(4)

without

without latching (only in connection with "Solenoid interlock monitored")

R

electrical latching force, typically 30 N

RE

electrically adjustable latching force 30 ... 100 N

(5)

M

permanent magnet, typically 15 N

Pictures


Product picture (catalogue individual photo)



ID: kmzm1f08

| 1.4 MB | .jpg | 216.253 x 833.261 mm - 613 x 2362 px - 72 dpi
| 235.7 kB | .png | 74.083 x 285.397 mm - 210 x 809 px - 72 dpi
| 28.1 kB | .jpg | 32.103 x 123.472 mm - 91 x 350 px - 72 dpi


Dimensional drawing basic component



ID: 1mzm1g14

| 20.7 kB | .swf |
| 5.2 kB | .png | 74.083 x 50.8 mm - 210 x 144 px - 72 dpi
| 160.8 kB | .jpg | 352.778 x 242.358 mm - 1000 x 687 px - 72 dpi

Dimensional drawing miscellaneous



ID: 1mzm1g15

| 12.9 kB | .swf |

| 290.8 kB | .jpg | 352.425 x 362.656 mm - 999 x 1028 px - 72 dpi

Schmersal, Inc., 15 Skyline Drive, Hawthorne, NY 10532

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 11/6/2023, 1:03 PM