

2	
/	

2			1								
480 Rated Voltage, 600 Max Voltage, High Z, Impedance.											
Part Numb	er Horsepov (HP)		r Maximu (A) Amps ( <i>J</i>	m Inductan A) (uH)	ce Weig (LB		s Available Lug Kit	Terminal Hole Size (Inches)			
KDRX2H	800	960	965	32.5	30	5 1661	SLK16	0.53			
480 Rated Voltage, 600 Max Voltage, Low Z, Impedance.											
Part Numb	Horsepow		r Maximu	um Inductan		ht Losse		Terminal Hole Size (Inches)			
KDRX2L	800	960	965	19.5	280	) 997	SLK16	0.53			
575 Rated Voltage, 600 Max Voltage, High Z, Impedance.											
Part Number	Horsepower (HP)	Motor Amps (A)		Inductance (uH)	Weight (LBS)	Losses (W)	Available Lug Kit	Terminal Hole Size (Inches)			
KDRX44H	800	768	864	49.8	310	1592	SLK16	0.53			
575 Rated Voltage, 600 Max Voltage, Low Z, Impedance.											
Part Number	Horsepower (HP)	Motor Amps (A)	Maximum Amps (A)	Inductance (uH)	Weight (LBS)	Losses (W)	Available Lug Kit	Terminal Hole Size (Inches)			
KDRX41L	900	864	900	26.6	280	1075	SLK16	0.53			
KDRX42L	1000	960	1000	23.9	280	1194	SLK16	0.53			