



LED Installation beacon MC55 with UL approval

The compact LED installation beacon 240 Multicolour from WERMA is now also available with UL approval required for the USA as well as the high protection rating IP69k. This continues the success story of this small, attention-grabbing product and enables it to be used under extreme conditions around the world.

240 LED Multicolour Beacon MC55



Technical Specifications

Dimensions (Ø x H)	55 mm x 46 mm (Protrusion from panel)
Housing	PC/ABS-Blend, black PC, black (UL approval)
Lens	PC, transparent
Fixing	Installation mounting M30
Colour options	Red, yellow, green, white, blue, violet, turquoise (RGB) Red, yellow, green (RGY)
Light effect	Permanent or Blinking light (1 Hz frequency)
Tone types and frequency	Pulse tone, 3400 Hz
Life duration light	Up to 50,000 h
Life duration buzzer	Up to 5,000 h



With buzzer

Protection rating	IP 65			
Sound output	85 dB (A)			
	Voltage	Current consumption	Plug M12	Cable
Tricolor (RGY)	24 V DC	45 mA	240 220 55	240 210 55
Multicolour (RGB)	10-30 V DC	60 mA	240 120 50	240 110 50

NEW

UL approval with buzzer

Protection rating	IP 69k			
	Voltage	Current consumption	Plug M12	
Tricolor (RGY)	24 V DC	65 mA	240 440 55	
Multicolour (RGB)	10-30 V DC	130 mA	240 340 50	



NEW

Without buzzer

Protection rating	IP 65			
	Voltage	Current consumption	Plug M12	Cable
Tricolor (RGY)	24 V DC	45 mA	240 240 55	240 230 55
Multicolour (RGB)	10-30 V DC	80 mA	240 140 50	240 130 50

UL approval without buzzer

Protection rating	IP 69k			
	Voltage	Current consumption	Plug M12	
Tricolor (RGY)	24 V DC	40 mA	240 420 55	
Multicolour (RGB)	10-30 V DC	120 mA	240 320 50	